


An entry level, high-capacity, high-performance LTO
Ultrium tape library for backup and archival solutions



IBM TotalStorage™ Ultrium Tape Library 3582



Highlights

- Offers capacity, performance, and reliability for midrange and network tape storage environments
- Provides a compact 4U standalone or rack mount configuration
- Patented multi-path architecture helps increase configuration flexibility with logical library partitioning
- Remote management capability is available through a Web browser
- Adheres to widely supported Linear Tape-Open™ (LTO) Ultrium™ design specifications
- Offers exclusive native switched fabric 2Gb Fibre Channel LTO Ultrium 2 Drives

IBM TotalStorage Ultrium Tape Library 3582

Today, all types of businesses rely on data as a key corporate asset. They want to be able to access data quickly and reliably, archive large databases and retrieve them when needed, and complete these tasks economically.

By fully leveraging advanced Linear Tape-Open (LTO) technology, the TotalStorage Ultrium Tape Library 3582 is designed to provide a cost-effective solution for handling a wide range of backup, archive, and disaster recovery data storage needs.

Advanced features

The IBM TotalStorage Ultrium Tape Library 3582 supports up to two IBM TotalStorage Ultrium 2 Tape Drives with up to 35 MB/sec native data transfer rates (70 MB/sec with 2:1 compression) per drive. It provides tape cartridge capacity up to 200GB native capacity (400GB with 2:1 compression) when using the new IBM TotalStorage LTO Ultrium 200GB Data Cartridge.

The IBM TotalStorage Ultrium 2 Tape Drives can read and write original LTO Ultrium data cartridges at first generation Ultrium 1 capacities with improved performance. The compact 4U 3582 Ultrium Tape Library is designed with a variety of advanced features. The new multi-path architecture is designed to

allow simultaneous attachment of heterogeneous servers and applications to LTO logical library partitions.

The 3582 Ultrium Tape Library has a barcode scanner for quick media verification and inventory. An LCD display on the front panel supports convenient local review of library status and provides control over local functions. LTO I/O expansion capability is available with a standard 1-cartridge I/O feature. Remote management capabilities using a Web browser provides library control and configuration. A control path failover for an AIX option is also available.

Software support

You can maximize the power of the IBM TotalStorage Ultrium Tape Library 3582 by managing it with industry-leading tape management solutions such as Tivoli® Storage Manager or other industry-recognized storage software.

Why IBM LTO?

IBM LTO Ultrium drives share best-of-breed technology. Advanced multi-track recording capabilities, state-of-the-art magneto-resistive (MR) heads, and a sophisticated track following servo system work together to produce extremely high recording densities. IBM Ultrium 2 drive enhancements include digital speed matching, power management, channel

IBM TotalStorage Ultrium Tape Library 3582 at a glance

Model number L23 Base Library with 23 cartridges, 1-I/O slot

Standalone feature code 2200

Rack-mount feature code 7003 rack mount kit

The IBM TotalStorage Ultrium Tape Library is a customer setup unit

Characteristics

Tape drive type IBM LTO Ultrium 2

Number of drives Up to 2

Number of tape cartridges 24

Capacity per cartridge¹ Up to 400 GB per cartridge compressed; 200 GB native
Up to 9.6TB per library compressed; 4.8TB native

Sustained data transfer rate¹ Up to 70 MB/sec compressed; 35 MB/sec native

Aggregate sustained data rate¹ Up to 494 GB/hour with two drives (compressed)

Media type IBM TotalStorage LTO Ultrium 200GB Data Cartridge (P/N 08L9870)
IBM TotalStorage LTO Universal Cleaning Cartridge (P/N 35L2086)

Dimensions 7.7" H x 17.9" W x 25.8" D (19.4 cm x 45.5 cm x 65.4 cm)

Weight 66.7 lb (30.3 kg) with two drives

Warranty Three year, Customer Replaceable Unit (CRU) in most countries

Operating environment

Temperature 10° to 38° C (50° to 100° F)

Relative humidity 20% to 80% (non-condensing)

Electrical power 1.5-0.6 amps (RMS) at 100-240 VAC, 50/60 Hz (max. configuration)

Attachment and systems support²

The IBM TotalStorage Ultrium Tape Library 3582 features native switched fabric 2Gb Fibre Channel, LVD Ultra 160 SCSI and HVD Ultra SCSI interfaces attaching to IBM @server pSeries™, IBM @server iSeries™, IBM @server xSeries™, RS/6000®, RS/6000 SP/AS/400®, and IBM Netfinity® systems, and non-IBM servers, workstations, and personal computers.

Operating systems support²

Device driver support is available for AIX®, OS/400®, Windows NT®, Windows® 2000; Windows Server® 2003; Sun Solaris; HP-UX; and Red Hat® and SuSE Linux®

¹ Based on 2:1 compression

² For latest information, consult Technical Support at www.ibm.com/storage/lto

calibration and 512 data tracks. Error correction code (ECC) function helps provide data integrity.

IBM and IBM authorized product resellers also provide service and technical support when you purchase an IBM LTO Ultrium solution—including a complete array of servers, software, printers, and storage devices.

Media

You can order media for the IBM TotalStorage Ultrium Tape Library 3582 at the time of purchase or from IBM Media, Supplies Distribution, and authorized dealers. Call 1-888-IBM-Media (1-888-426-6334) toll-free in the United States and Canada.

For more information

For more information, contact your IBM representative or IBM Business Partner. For updated attachment, supported operating system, media product, and storage management software information, visit www.ibm.com/totalstorage/lto.



© International Business Machines Corporation 2003

IBM Systems Group
9000 S. Rita Road
Tucson, AZ 85744
United States

Produced in the United States
05-03
All Rights Reserved

IBM, AIX, AS/400, @server, iSeries, Netfinity, OS/400, pSeries, RS/6000, and xSeries are registered trademarks of International Business Machines Corporation.

Linear Tape-Open, LTO, the LTO logo, Ultrium, and the Ultrium logo are U.S. trademarks of HP, and IBM. Tivoli is a registered trademark of Tivoli Systems, Inc. Windows and Windows NT are registered trademarks of Microsoft Corporation. Other company, product, and service names may be trademarks or registered trademarks of their respective companies.

Other company, product, and service names may be trademarks or service marks of others.

References in this publication to IBM products or services do not imply that IBM intends to make them available in all countries in which IBM operates.

IBM hardware products are manufactured from new parts, or new and used parts. In some cases, the hardware product may not be new and may have been previously installed. Regardless, IBM warranty terms apply.

Product data is accurate as of initial publication and is subject to change without notice.

Photography depicts design models. Actual product may show slight variations.

GB equals one billion bytes when referring to hard drive capacity; accessible capacity may be less.

G225-6977-00